



## Eyelet Connection Technique

Machine: appropriate for yarn

Yarn: your choice

Tension: appropriate for yarn

Gauge: to be determined

Section 1:

E-wrap cast on appropriate number of stitches for  $\frac{1}{2}$  the desired width.

Knit 20 rows.

\* On carriage side, make an eyelet by transferring the 3<sup>rd</sup> stitch in to the 4<sup>th</sup> needle (there will be 2 stitches on the 4<sup>th</sup> needle, 0 stitches on the 3<sup>rd</sup> needle, and 1 stitch of each of the end 2 needles). Make sure empty needle is in work.

Knit 20 rows \*

Repeat from \* to \* to desired length. Bind off.

Section 2:

E-wrap cast on appropriate number of stitches for ½ the desired width.

Knit 20R.

\*\* Opposite the carriage side, make an eyelet by transferring the 3<sup>rd</sup> stitch to the 4<sup>th</sup> needle (there will be 1 stitch of each of the end 2 needles , 0 stitches on the 3<sup>rd</sup> needle, and 2 stitches on the 4<sup>th</sup> needle). Make sure empty needle is in work.

AT THE SAME TIME with purl side of section 1 facing you, insert a 2-prong tool into the 1<sup>st</sup> eyelet and remove the 2 end stitches opposite the carriage from the machine. Carefully pull your tool through the eyelet and replace stitches back onto the same needles.



Knit 20 rows. \*\*

Repeat from \*\* to \*\* for desired length, moving up an eyelet on Section 1 every 20 rows.

Bind off.